

# POLYTOUCH® CLASSIC 32

is the expandable all in one kiosk system from Pyramid. Product features and visual content can be conveniently presented at the POS thanks to the 32" multitouch Full HD screen.

The innovative, highly flexible Quick Mounting System (QMS) offers a unique selling proposition, with which the installed hardware peripherals can be easily replaced. This guarantees longevity and a high level of maintenance and service of the solution. In addition, a lettering of the side panels with a LED signage make it possible to create a CI-compliant product.



## DISPLAY

Screen size	812.8 mm (31.5") (Anti Glare)
Resolution	1920 x 1080 (Full HD)
Brightness	450 cd/m <sup>2</sup>
Contrast	3000 : 1
Touch technology	Projected capacitive technology (PCT) (10 touches)
Latency	< 25 ms

## COMPUTER UNIT

Processor	Intel® Core™ i5-4570TE Haswell (2.7 GHz [Turbo: 3.3 GHz] / 4 MB cache / 2 cores / 4 threads)
Chipset	Intel® Q87 Express
Graphics	Intel® HD4600 graphics on Chip (350 MHz [Turbo: 1 GHz])
Memory	8 GB DDR-3 PC1600
Storage	mSATA SSD 128 GB
LAN / WLAN	1GbE LAN / 300 Mbps WLAN
OS compatibility	Windows 7 (32/64 Bit), Windows 8 (32/64 Bit), Ubuntu Linux

## POWER

Power input	100-240 V AC C14
-------------	------------------

## SYSTEM

Dimensions (WxDxH)	Slim modules: 951 x 446 x 83 mm/37.44 x 17.56 x 3.27 inch QMS modules: 1042 x 446 x 82 mm/41.02 x 17.56 x 3.23 inch (with POS thermal print: 1042 x 446 x 88 mm/41.02 x 17.56 x 3.46 inch)
System weight	27 kg (without packaging and pedestal)
Mounting	VESA MIS-E; wall-mount, built-in, pedestal

## ENVIRONMENTAL CONDITIONS

	Storage	Operating
Temperature	5°C to 60°C	10°C to 35°C
Humidity	5% to 95% <sup>1</sup>	20% to 90% <sup>1</sup>

<sup>1</sup> non-condensing

## CONFIGURATION

Printer	80x80 POS thermal printer
Payment module	e.g. Verifone VX820
Scanner	e.g. Honeywell N5680
RFID/NFC reader	

## DIMENSIONS

