

POLYTOUCH® PASSPORT 27

The dual sided kiosk is optimized for a high workload capacity. This is especially interesting for qsr's, restaurants, bakeries, cinemas or other brick and mortar stores. It ensures less queues for customers during peak times while optimizing the order and payment process. With the miniaturized footprint, it was never easier to implement an all in one kiosk solution into existing store concepts. The distinctive pedestal provides the kiosk with a unique look, making it a real designer piece, with its clear contours and sleek appearance convincing even non-tech-savvy customers of the benefits of self-service. A pole light (optional) ensures that the system attracts customers' attention even in heavily frequented areas. Outside the peak times, the customer can activate the pole light at the push of a button to request assistance or advice from the staff.



DISPLAY

Screen size	685.65 mm (27.0")
Viewing Angle (CR>10)	R/L 178 U/D 178
Resolution	1920 x 1080 (Full HD)
Luminance	300 cd/m ²
Coating	Glare or Antiglare
Touch technology	Projected capacitive touch (PCT) with 10 touches
Latency	<10 ms
Processor	Intel® Core™ i5-6500T Skylake 4C/4T 2.5 Ghz 6 MB

COMPUTER UNIT

Chipset	Intel® Q170 chipset
Graphics	Intel® HD530 graphics
Memory	8 GB DDR4 (up to 16 GB)

POWER

Input voltage	100-240 V AC, 50-60 Hz
Power consumption	Idle 60 W, load 100 W*

*depending on configuration

SYSTEM

Material System	Steel powder coated RAL 9005, 9007, 9010
Dimensions (WxHxD)	420 x 2252 x 488 mm/16.54 x 88.66 x 19.21 inch
Mounting	Design Pedestal

ENVIRONMENTAL CONDITIONS

	Storage	Operating
Temperature	5°C to 60°C	10°C to 35°C
Humidity	5% to 95% ¹	20% to 90% ¹

¹ non-condensing

CONFIGURATION

Imager	Honeywell CM3680*
Payment terminal	Verifone MX915*
Printer	Epson TM-T88V*

*optional

DIMENSIONS

